OpenID Certification Submission Examples v1.0

OpenID Connect Working Group, OpenID Foundation

April 2, 2015

1. Introduction

This document contains examples of the contents of several sample certification submissions. While every attempt has been made to make contents of these examples accurate, the sets of tests and requirements stated in the testing suite at op.certification.openid.net are authoritative. See the certification submission procedures for how to make a certification request.

2. Example Certification Submissions

2.1 OpenID Provider Conformance Profile Submission Examples

2.1.1 Basic OpenID Provider

In this example, the ProseWare organization is requesting certification of its "Humongous Identity" software to the Basic OpenID Provider profile on April 13, 2015. It submits this zip file as an attachment:

```
ProseWare-Humongous_Identity-OP-Basic-13-Apr-2015.zip
```

with the following contents:

```
code.config.static.sign/OP-claims-essential.html
code.config.static.sign/OP-ClientAuth-Basic-Static.html
code.config.static.sign/OP-ClientAuth-SecretPost-Static.html
code.config.static.sign/OP-display-page.html
code.config.static.sign/OP-display-popup.html
code.config.static.sign/OP-IDToken-kid.html
code.config.static.sign/OP-IDToken-Signature.html
code.config.static.sign/OP-nonce-code.html
code.config.static.sign/OP-nonce-NoReq-code.html
code.config.static.sign/OP-OAuth-2nd-30s.html
code.config.static.sign/OP-OAuth-2nd-Revokes.html
```

```
code.config.static.sign/OP-OAuth-2nd.html
code.config.static.sign/OP-prompt-login.html
code.config.static.sign/OP-prompt-login.png
code.config.static.sign/OP-prompt-none-LoggedIn.html
code.config.static.sign/OP-prompt-none-NotLoggedIn.html
code.config.static.sign/OP-redirect_uri-NotReg.html
code.config.static.sign/OP-redirect_uri-NotReg.png
code.config.static.sign/OP-Req-acr_values.html
code.config.static.sign/OP-Req-claims_locales.html
code.config.static.sign/OP-Req-id_token_hint.html
code.config.static.sign/OP-Req-login_hint.html
code.config.static.sign/OP-Req-max_age=1.html
code.config.static.sign/OP-Req-max_age=1.png
code.config.static.sign/OP-Req-max_age=10000.html
code.config.static.sign/OP-Req-NotUnderstood.html
code.config.static.sign/OP-Req-ui_locales.html
code.config.static.sign/OP-request-Unsigned.html
code.config.static.sign/OP-request_uri-Unsigned.html
code.config.static.sign/OP-Response-code.html
code.config.static.sign/OP-Response-Missing.html
code.config.static.sign/OP-Response-Missing.png
code.config.static.sign/OP-scope-address.html
code.config.static.sign/OP-scope-All.html
code.config.static.sign/OP-scope-email.html
code.config.static.sign/OP-scope-phone.html
code.config.static.sign/OP-scope-profile.html
code.config.static.sign/OP-UserInfo-Body.html
code.config.static.sign/OP-UserInfo-Endpoint.html
code.config.static.sign/OP-UserInfo-Header.html
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf
```

Note that if dynamic registration is supported, the ".static." in the log file paths above will instead be ".dynamic." and a slightly different set of tests for this profile will be presented by the test tool. For instance, the OP-ClientAuth-Basic-Static test will be replaced with OP-ClientAuth-Basic-Dynamic. Example contents of a submission for the Basic profile when dynamic registration is supported are:

```
code.config.dynamic.sign/OP-claims-essential.html
code.config.dynamic.sign/OP-ClientAuth-Basic-Dynamic.html
code.config.dynamic.sign/OP-ClientAuth-SecretPost-Dynamic.html
code.config.dynamic.sign/OP-display-page.html
```

```
code.config.dynamic.sign/OP-display-popup.html
code.config.dynamic.sign/OP-IDToken-kid.html
code.config.dynamic.sign/OP-nonce-code.html
code.config.dynamic.sign/OP-nonce-NoReq-code.html
code.config.dynamic.sign/OP-OAuth-2nd-30s.html
code.config.dynamic.sign/OP-OAuth-2nd-Revokes.html
code.config.dynamic.sign/OP-OAuth-2nd.html
code.config.dynamic.sign/OP-prompt-login.html
code.config.dynamic.sign/OP-prompt-login.png
code.config.dynamic.sign/OP-prompt-none-LoggedIn.html
code.config.dynamic.sign/OP-prompt-none-NotLoggedIn.html
code.config.dynamic.sign/OP-redirect_uri-NotReg.html
code.config.dynamic.sign/OP-redirect_uri-NotReg.png
code.config.dynamic.sign/OP-Req-acr_values.html
code.config.dynamic.sign/OP-Req-claims_locales.html
code.config.dynamic.sign/OP-Req-id_token_hint.html
code.config.dynamic.sign/OP-Req-login_hint.html
code.config.dynamic.sign/OP-Req-max_age=1.html
code.config.dynamic.sign/OP-Req-max_age=1.png
code.config.dynamic.sign/OP-Req-max_age=10000.html
code.config.dynamic.sign/OP-Req-NotUnderstood.html
code.config.dynamic.sign/OP-Req-ui_locales.html
code.config.dynamic.sign/OP-request-Unsigned.html
code.config.dynamic.sign/OP-request_uri-Unsigned-Dynamic.html
code.config.dynamic.sign/OP-Response-code.html
code.config.dynamic.sign/OP-Response-Missing.html
code.config.dynamic.sign/OP-Response-Missing.png
code.config.dynamic.sign/OP-scope-address.html
code.config.dynamic.sign/OP-scope-All.html
code.config.dynamic.sign/OP-scope-email.html
code.config.dynamic.sign/OP-scope-phone.html
code.config.dynamic.sign/OP-scope-profile.html
code.config.dynamic.sign/OP-UserInfo-Body.html
code.config.dynamic.sign/OP-UserInfo-Endpoint.html
code.config.dynamic.sign/OP-UserInfo-Header.html
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf
```

Similarly, if only signing with “none” is supported, the “.sign” will instead be “.none” and the test OP-IDToken-kid will be omitted. Example contents of a submission for the Basic profile when only unsigned ID Tokens are supported are:

```
code.config.static.none/OP-claims-essential.html
code.config.static.none/OP-ClientAuth-Basic-Static.html
code.config.static.none/OP-ClientAuth-SecretPost-Static.html
code.config.static.none/OP-display-page.html
code.config.static.none/OP-display-popup.html
code.config.static.none/OP-IDToken-Signature.html
code.config.static.none/OP-nonce-code.html
code.config.static.none/OP-nonce-NoReq-code.html
code.config.static.none/OP-OAuth-2nd-30s.html
code.config.static.none/OP-OAuth-2nd-Revokes.html
code.config.static.none/OP-OAuth-2nd.html
code.config.static.none/OP-prompt-login.html
code.config.static.none/OP-prompt-login.png
code.config.static.none/OP-prompt-none-LoggedIn.html
code.config.static.none/OP-prompt-none-NotLoggedIn.html
code.config.static.none/OP-redirect_uri-NotReg.html
code.config.static.none/OP-redirect_uri-NotReg.png
code.config.static.none/OP-Req-acr_values.html
code.config.static.none/OP-Req-claims_locales.html
code.config.static.none/OP-Req-id_token_hint.html
code.config.static.none/OP-Req-login_hint.html
code.config.static.none/OP-Req-max_age=1.html
code.config.static.none/OP-Req-max_age=1.png
code.config.static.none/OP-Req-max_age=10000.html
code.config.static.none/OP-Req-NotUnderstood.html
code.config.static.none/OP-Req-ui_locales.html
code.config.static.none/OP-request-Unsigned.html
code.config.static.none/OP-request_uri-Unsigned.html
code.config.static.none/OP-Response-code.html
code.config.static.none/OP-Response-Missing.html
code.config.static.none/OP-Response-Missing.png
code.config.static.none/OP-scope-address.html
code.config.static.none/OP-scope-All.html
code.config.static.none/OP-scope-email.html
code.config.static.none/OP-scope-phone.html
code.config.static.none/OP-scope-profile.html
code.config.static.none/OP-UserInfo-Body.html
code.config.static.none/OP-UserInfo-Endpoint.html
code.config.static.none/OP-UserInfo-Header.html
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf
```

2.1.2 Implicit OpenID Provider

In this example, the ProseWare organization is requesting certification of its "Humongous Identity" software to the Implicit OpenID Provider profile on April 13, 2015. It submits this zip file as an attachment:

```
ProseWare-Humongous_Identity-OP-Implicit-13-Apr-2015.zip
```

with the following contents:

```
id_token.config.static.sign/OP-display-page.html
id_token.config.static.sign/OP-display-popup.html
id_token.config.static.sign/OP-IDToken-kid.html
id_token.config.static.sign/OP-IDToken-Signature.html
id_token.config.static.sign/OP-nonce-noncode.html
id_token.config.static.sign/OP-nonce-NoReq-noncode.html
id_token.config.static.sign/OP-prompt-login.html
id_token.config.static.sign/OP-prompt-login.png
id_token.config.static.sign/OP-prompt-none-LoggedIn.html
id_token.config.static.sign/OP-prompt-none-NotLoggedIn.html
id_token.config.static.sign/OP-redirect_uri-NotReg.html
id_token.config.static.sign/OP-redirect_uri-NotReg.png
id_token.config.static.sign/OP-Req-acr_values.html
id_token.config.static.sign/OP-Req-claims_locales.html
id_token.config.static.sign/OP-Req-id_token_hint.html
id_token.config.static.sign/OP-Req-login_hint.html
id_token.config.static.sign/OP-Req-max_age=1.html
id_token.config.static.sign/OP-Req-max_age=1.png
id_token.config.static.sign/OP-Req-max_age=10000.html
id_token.config.static.sign/OP-Req-NotUnderstood.html
id_token.config.static.sign/OP-Req-ui_locales.html
id_token.config.static.sign/OP-request-Unsigned.html
id_token.config.static.sign/OP-request_uri-Unsigned.html
id_token.config.static.sign/OP-Response-id_token.html
id_token.config.static.sign/OP-Response-Missing.html
id_token.config.static.sign/OP-Response-Missing.png
id_token.config.static.sign/OP-scope-address.html
id_token.config.static.sign/OP-scope-All.html
id_token.config.static.sign/OP-scope-email.html
id_token.config.static.sign/OP-scope-phone.html
id_token.config.static.sign/OP-scope-profile.html
id_token+token.config.static.sign/OP-claims-essential.html
```

id_token+token.config.static.sign/OP-display-page.html
id_token+token.config.static.sign/OP-display-popup.html
id_token+token.config.static.sign/OP-IDToken-at_hash.html
id_token+token.config.static.sign/OP-IDToken-kid.html
id_token+token.config.static.sign/OP-IDToken-Signature.html
id_token+token.config.static.sign/OP-nonce-noncode.html
id_token+token.config.static.sign/OP-nonce-NoReq-noncode.html
id_token+token.config.static.sign/OP-prompt-login.html
id_token+token.config.static.sign/OP-prompt-login.png
id_token+token.config.static.sign/OP-prompt-none-LoggedIn.html
id_token+token.config.static.sign/OP-prompt-none-NotLoggedIn.html
id_token+token.config.static.sign/OP-redirect_uri-NotReg.html
id_token+token.config.static.sign/OP-redirect_uri-NotReg.png
id_token+token.config.static.sign/OP-Req-acr_values.html
id_token+token.config.static.sign/OP-Req-claims_locales.html
id_token+token.config.static.sign/OP-Req-id_token_hint.html
id_token+token.config.static.sign/OP-Req-login_hint.html
id_token+token.config.static.sign/OP-Req-max_age=1.html
id_token+token.config.static.sign/OP-Req-max_age=1.png
id_token+token.config.static.sign/OP-Req-max_age=10000.html
id_token+token.config.static.sign/OP-Req-NotUnderstood.html
id_token+token.config.static.sign/OP-Req-ui_locales.html
id_token+token.config.static.sign/OP-request-Unsigned.html
id_token+token.config.static.sign/OP-request_uri-Unsigned.html
id_token+token.config.static.sign/OP-Response-id_token+token.html
id_token+token.config.static.sign/OP-Response-Missing.html
id_token+token.config.static.sign/OP-Response-Missing.png
id_token+token.config.static.sign/OP-scope-address.html
id_token+token.config.static.sign/OP-scope-All.html
id_token+token.config.static.sign/OP-scope-email.html
id_token+token.config.static.sign/OP-scope-phone.html
id_token+token.config.static.sign/OP-scope-profile.html
id_token+token.config.static.sign/OP-UserInfo-Body.html
id_token+token.config.static.sign/OP-UserInfo-Endpoint.html
id_token+token.config.static.sign/OP-UserInfo-Header.html
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf

Note that if dynamic registration is supported, the ".static." in the log file paths above will instead be ".dynamic." and a slightly different set of tests for this profile will be presented by the test tool. For instance, the OP-ClientAuth-Basic-Static test will be replaced with OP-ClientAuth-Basic-Dynamic. Example contents of a submission for the Implicit profile when dynamic registration is supported are:

```
id_token.config.dynamic.sign/OP-display-page.html
id_token.config.dynamic.sign/OP-display-popup.html
id_token.config.dynamic.sign/OP-IDToken-kid.html
id_token.config.dynamic.sign/OP-nonce-noncode.html
id_token.config.dynamic.sign/OP-nonce-NoReq-noncode.html
id_token.config.dynamic.sign/OP-prompt-login.html
id_token.config.dynamic.sign/OP-prompt-login.png
id_token.config.dynamic.sign/OP-prompt-none-LoggedIn.html
id_token.config.dynamic.sign/OP-prompt-none-NotLoggedIn.html
id_token.config.dynamic.sign/OP-redirect_uri-NotReg.html
id_token.config.dynamic.sign/OP-redirect_uri-NotReg.png
id_token.config.dynamic.sign/OP-Req-acr_values.html
id_token.config.dynamic.sign/OP-Req-claims_locales.html
id_token.config.dynamic.sign/OP-Req-id_token_hint.html
id_token.config.dynamic.sign/OP-Req-login_hint.html
id_token.config.dynamic.sign/OP-Req-max_age=1.html
id_token.config.dynamic.sign/OP-Req-max_age=1.png
id_token.config.dynamic.sign/OP-Req-max_age=10000.html
id_token.config.dynamic.sign/OP-Req-NotUnderstood.html
id_token.config.dynamic.sign/OP-Req-ui_locales.html
id_token.config.dynamic.sign/OP-request-Unsigned.html
id_token.config.dynamic.sign/OP-request_uri-Unsigned-Dynamic.html
id_token.config.dynamic.sign/OP-Response-id_token.html
id_token.config.dynamic.sign/OP-Response-Missing.html
id_token.config.dynamic.sign/OP-Response-Missing.png
id_token.config.dynamic.sign/OP-scope-address.html
id_token.config.dynamic.sign/OP-scope-All.html
id_token.config.dynamic.sign/OP-scope-email.html
id_token.config.dynamic.sign/OP-scope-phone.html
id_token.config.dynamic.sign/OP-scope-profile.html
id_token+token.config.dynamic.sign/OP-claims-essential.html
id_token+token.config.dynamic.sign/OP-display-page.html
id_token+token.config.dynamic.sign/OP-display-popup.html
id_token+token.config.dynamic.sign/OP-IDToken-at_hash.html
id_token+token.config.dynamic.sign/OP-IDToken-kid.html
id_token+token.config.dynamic.sign/OP-nonce-noncode.html
```

```
id_token+token.config.dynamic.sign/OP-nonce-NoReq-noncode.html
id_token+token.config.dynamic.sign/OP-prompt-login.html
id_token+token.config.dynamic.sign/OP-prompt-login.png
id_token+token.config.dynamic.sign/OP-prompt-none-LoggedIn.html
id_token+token.config.dynamic.sign/OP-prompt-none-NotLoggedIn.html
id_token+token.config.dynamic.sign/OP-redirect_uri-NotReg.html
id_token+token.config.dynamic.sign/OP-redirect_uri-NotReg.png
id_token+token.config.dynamic.sign/OP-Req-acr_values.html
id_token+token.config.dynamic.sign/OP-Req-claims_locales.html
id_token+token.config.dynamic.sign/OP-Req-id_token_hint.html
id_token+token.config.dynamic.sign/OP-Req-login_hint.html
id_token+token.config.dynamic.sign/OP-Req-max_age=1.html
id_token+token.config.dynamic.sign/OP-Req-max_age=1.png
id_token+token.config.dynamic.sign/OP-Req-max_age=10000.html
id_token+token.config.dynamic.sign/OP-Req-NotUnderstood.html
id_token+token.config.dynamic.sign/OP-Req-ui_locales.html
id_token+token.config.dynamic.sign/OP-request-Unsigned.html
id_token+token.config.dynamic.sign/OP-request_uri-Unsigned-Dynamic.html
id_token+token.config.dynamic.sign/OP-Response-id_token+token.html
id_token+token.config.dynamic.sign/OP-Response-Missing.html
id_token+token.config.dynamic.sign/OP-Response-Missing.png
id_token+token.config.dynamic.sign/OP-scope-address.html
id_token+token.config.dynamic.sign/OP-scope-All.html
id_token+token.config.dynamic.sign/OP-scope-email.html
id_token+token.config.dynamic.sign/OP-scope-phone.html
id_token+token.config.dynamic.sign/OP-scope-profile.html
id_token+token.config.dynamic.sign/OP-UserInfo-Body.html
id_token+token.config.dynamic.sign/OP-UserInfo-Endpoint.html
id_token+token.config.dynamic.sign/OP-UserInfo-Header.html
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf
```

2.1.3 Hybrid OpenID Provider

In this example, the ProseWare organization is requesting certification of its "Humongous Identity" software to the Hybrid OpenID Provider profile on April 13, 2015. It submits this zip file as an attachment:

```
ProseWare-Humongous_Identity-OP-Hybrid-13-Apr-2015.zip
```

with the following contents:

```
code+id_token.config.static.sign/OP-claims-essential.html
code+id_token.config.static.sign/OP-ClientAuth-Basic-Static.html
code+id_token.config.static.sign/OP-ClientAuth-SecretPost-Static.html
code+id_token.config.static.sign/OP-display-page.html
code+id_token.config.static.sign/OP-display-popup.html
code+id_token.config.static.sign/OP-IDToken-c_hash.html
code+id_token.config.static.sign/OP-IDToken-kid.html
code+id_token.config.static.sign/OP-IDToken-Signature.html
code+id_token.config.static.sign/OP-nonce-noncode.html
code+id_token.config.static.sign/OP-OAuth-2nd-30s.html
code+id_token.config.static.sign/OP-OAuth-2nd-Revokes.html
code+id_token.config.static.sign/OP-OAuth-2nd.html
code+id_token.config.static.sign/OP-prompt-login.html
code+id_token.config.static.sign/OP-prompt-login.png
code+id_token.config.static.sign/OP-prompt-none-LoggedIn.html
code+id_token.config.static.sign/OP-prompt-none-NotLoggedIn.html
code+id_token.config.static.sign/OP-redirect_uri-NotReg.html
code+id_token.config.static.sign/OP-redirect_uri-NotReg.png
code+id_token.config.static.sign/OP-Req-acr_values.html
code+id_token.config.static.sign/OP-Req-claims_locales.html
code+id_token.config.static.sign/OP-Req-id_token_hint.html
code+id_token.config.static.sign/OP-Req-login_hint.html
code+id_token.config.static.sign/OP-Req-max_age=1.html
code+id_token.config.static.sign/OP-Req-max_age=1.png
code+id_token.config.static.sign/OP-Req-max_age=10000.html
code+id_token.config.static.sign/OP-Req-NotUnderstood.html
code+id_token.config.static.sign/OP-Req-ui_locales.html
code+id_token.config.static.sign/OP-request-Unsigned.html
code+id_token.config.static.sign/OP-request_uri-Unsigned.html
code+id_token.config.static.sign/OP-Response-code+id_token.html
code+id_token.config.static.sign/OP-Response-Missing.html
code+id_token.config.static.sign/OP-Response-Missing.png
code+id_token.config.static.sign/OP-scope-address.html
code+id_token.config.static.sign/OP-scope-All.html
code+id_token.config.static.sign/OP-scope-email.html
code+id_token.config.static.sign/OP-scope-phone.html
code+id_token.config.static.sign/OP-scope-profile.html
code+id_token.config.static.sign/OP-UserInfo-Body.html
code+id_token.config.static.sign/OP-UserInfo-Endpoint.html
code+id_token.config.static.sign/OP-UserInfo-Header.html
code+id_token+token.config.static.sign/OP-claims-essential.html
```

code+id_token+token.config.static.sign/OP-ClientAuth-Basic-Static.html
code+id_token+token.config.static.sign/OP-ClientAuth-SecretPost-Static.html
code+id_token+token.config.static.sign/OP-display-page.html
code+id_token+token.config.static.sign/OP-display-popup.html
code+id_token+token.config.static.sign/OP-IDToken-at_hash.html
code+id_token+token.config.static.sign/OP-IDToken-c_hash.html
code+id_token+token.config.static.sign/OP-IDToken-kid.html
code+id_token+token.config.static.sign/OP-IDToken-Signature.html
code+id_token+token.config.static.sign/OP-nonce-noncode.html
code+id_token+token.config.static.sign/OP-OAuth-2nd-30s.html
code+id_token+token.config.static.sign/OP-OAuth-2nd-Revokes.html
code+id_token+token.config.static.sign/OP-OAuth-2nd.html
code+id_token+token.config.static.sign/OP-prompt-login.html
code+id_token+token.config.static.sign/OP-prompt-login.png
code+id_token+token.config.static.sign/OP-prompt-none-LoggedIn.html
code+id_token+token.config.static.sign/OP-prompt-none-NotLoggedIn.html
code+id_token+token.config.static.sign/OP-redirect_uri-NotReg.html
code+id_token+token.config.static.sign/OP-redirect_uri-NotReg.png
code+id_token+token.config.static.sign/OP-Req-acr_values.html
code+id_token+token.config.static.sign/OP-Req-claims_locales.html
code+id_token+token.config.static.sign/OP-Req-id_token_hint.html
code+id_token+token.config.static.sign/OP-Req-login_hint.html
code+id_token+token.config.static.sign/OP-Req-max_age=1.html
code+id_token+token.config.static.sign/OP-Req-max_age=1.png
code+id_token+token.config.static.sign/OP-Req-max_age=10000.html
code+id_token+token.config.static.sign/OP-Req-NotUnderstood.html
code+id_token+token.config.static.sign/OP-Req-ui_locales.html
code+id_token+token.config.static.sign/OP-request-Unsigned.html
code+id_token+token.config.static.sign/OP-request_uri-Unsigned.html
code+id_token+token.config.static.sign/OP-Response-code+id_token+token.html
code+id_token+token.config.static.sign/OP-Response-Missing.html
code+id_token+token.config.static.sign/OP-Response-Missing.png
code+id_token+token.config.static.sign/OP-scope-address.html
code+id_token+token.config.static.sign/OP-scope-All.html
code+id_token+token.config.static.sign/OP-scope-email.html
code+id_token+token.config.static.sign/OP-scope-phone.html
code+id_token+token.config.static.sign/OP-scope-profile.html
code+id_token+token.config.static.sign/OP-UserInfo-Body.html
code+id_token+token.config.static.sign/OP-UserInfo-Endpoint.html
code+id_token+token.config.static.sign/OP-UserInfo-Header.html
code+token.config.static.sign/OP-claims-essential.html

code+token.config.static.sign/OP-ClientAuth-Basic-Static.html
code+token.config.static.sign/OP-ClientAuth-SecretPost-Static.html
code+token.config.static.sign/OP-display-page.html
code+token.config.static.sign/OP-display-popup.html
code+token.config.static.sign/OP-IDToken-kid.html
code+token.config.static.sign/OP-IDToken-Signature.html
code+token.config.static.sign/OP-nonce-noncode.html
code+token.config.static.sign/OP-nonce-NoReq-code.html
code+token.config.static.sign/OP-OAuth-2nd-30s.html
code+token.config.static.sign/OP-OAuth-2nd-Revokes.html
code+token.config.static.sign/OP-OAuth-2nd.html
code+token.config.static.sign/OP-prompt-login.html
code+token.config.static.sign/OP-prompt-login.png
code+token.config.static.sign/OP-prompt-none-LoggedIn.html
code+token.config.static.sign/OP-prompt-none-NotLoggedIn.html
code+token.config.static.sign/OP-redirect_uri-NotReg.html
code+token.config.static.sign/OP-redirect_uri-NotReg.png
code+token.config.static.sign/OP-Req-acr_values.html
code+token.config.static.sign/OP-Req-claims_locales.html
code+token.config.static.sign/OP-Req-id_token_hint.html
code+token.config.static.sign/OP-Req-login_hint.html
code+token.config.static.sign/OP-Req-max_age=1.html
code+token.config.static.sign/OP-Req-max_age=1.png
code+token.config.static.sign/OP-Req-max_age=10000.html
code+token.config.static.sign/OP-Req-NotUnderstood.html
code+token.config.static.sign/OP-Req-ui_locales.html
code+token.config.static.sign/OP-request-Unsigned.html
code+token.config.static.sign/OP-request_uri-Unsigned.html
code+token.config.static.sign/OP-Response-code+token.html
code+token.config.static.sign/OP-Response-Missing.html
code+token.config.static.sign/OP-Response-Missing.png
code+token.config.static.sign/OP-scope-address.html
code+token.config.static.sign/OP-scope-All.html
code+token.config.static.sign/OP-scope-email.html
code+token.config.static.sign/OP-scope-phone.html
code+token.config.static.sign/OP-scope-profile.html
code+token.config.static.sign/OP-UserInfo-Body.html
code+token.config.static.sign/OP-UserInfo-Endpoint.html
code+token.config.static.sign/OP-UserInfo-Header.html
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf

Note that if dynamic registration is supported, the ".static." in the log file paths above will instead be ".dynamic." and a slightly different set of tests for this profile will be presented by the test tool. For instance, the OP-ClientAuth-Basic-Static test will be replaced with OP-ClientAuth-Basic-Dynamic. Example contents of a submission for the Hybrid profile when dynamic registration is supported are:

```
code+id_token.config.dynamic.sign/OP-claims-essential.html
code+id_token.config.dynamic.sign/OP-ClientAuth-Basic-Dynamic.html
code+id_token.config.dynamic.sign/OP-ClientAuth-SecretPost-Dynamic.html
code+id_token.config.dynamic.sign/OP-display-page.html
code+id_token.config.dynamic.sign/OP-display-popup.html
code+id_token.config.dynamic.sign/OP-IDToken-c_hash.html
code+id_token.config.dynamic.sign/OP-IDToken-kid.html
code+id_token.config.dynamic.sign/OP-nonce-noncode.html
code+id_token.config.dynamic.sign/OP-OAuth-2nd-30s.html
code+id_token.config.dynamic.sign/OP-OAuth-2nd-Revokes.html
code+id_token.config.dynamic.sign/OP-OAuth-2nd.html
code+id_token.config.dynamic.sign/OP-prompt-login.html
code+id_token.config.dynamic.sign/OP-prompt-login.png
code+id_token.config.dynamic.sign/OP-prompt-none-LoggedIn.html
code+id_token.config.dynamic.sign/OP-prompt-none-NotLoggedIn.html
code+id_token.config.dynamic.sign/OP-redirect_uri-NotReg.html
code+id_token.config.dynamic.sign/OP-redirect_uri-NotReg.png
code+id_token.config.dynamic.sign/OP-Req-acr_values.html
code+id_token.config.dynamic.sign/OP-Req-claims_locales.html
code+id_token.config.dynamic.sign/OP-Req-id_token_hint.html
code+id_token.config.dynamic.sign/OP-Req-login_hint.html
code+id_token.config.dynamic.sign/OP-Req-max_age=1.html
code+id_token.config.dynamic.sign/OP-Req-max_age=1.png
code+id_token.config.dynamic.sign/OP-Req-max_age=10000.html
code+id_token.config.dynamic.sign/OP-Req-NotUnderstood.html
code+id_token.config.dynamic.sign/OP-Req-ui_locales.html
code+id_token.config.dynamic.sign/OP-request-Unsigned.html
code+id_token.config.dynamic.sign/OP-request_uri-Unsigned-Dynamic.html
code+id_token.config.dynamic.sign/OP-Response-code+id_token.html
code+id_token.config.dynamic.sign/OP-Response-Missing.html
code+id_token.config.dynamic.sign/OP-Response-Missing.png
code+id_token.config.dynamic.sign/OP-scope-address.html
code+id_token.config.dynamic.sign/OP-scope-All.html
code+id_token.config.dynamic.sign/OP-scope-email.html
code+id_token.config.dynamic.sign/OP-scope-phone.html
code+id_token.config.dynamic.sign/OP-scope-profile.html
```

```
code+id_token.config.dynamic.sign/OP-UserInfo-Body.html
code+id_token.config.dynamic.sign/OP-UserInfo-Endpoint.html
code+id_token.config.dynamic.sign/OP-UserInfo-Header.html
code+id_token+token.config.dynamic.sign/OP-claims-essential.html
code+id_token+token.config.dynamic.sign/OP-ClientAuth-Basic-Dynamic.html
code+id_token+token.config.dynamic.sign/OP-ClientAuth-SecretPost-Dynamic.html
code+id_token+token.config.dynamic.sign/OP-display-page.html
code+id_token+token.config.dynamic.sign/OP-display-popup.html
code+id_token+token.config.dynamic.sign/OP-IDToken-at_hash.html
code+id_token+token.config.dynamic.sign/OP-IDToken-c_hash.html
code+id_token+token.config.dynamic.sign/OP-IDToken-kid.html
code+id_token+token.config.dynamic.sign/OP-nonce-noncode.html
code+id_token+token.config.dynamic.sign/OP-OAuth-2nd-30s.html
code+id_token+token.config.dynamic.sign/OP-OAuth-2nd-Revokes.html
code+id_token+token.config.dynamic.sign/OP-OAuth-2nd.html
code+id_token+token.config.dynamic.sign/OP-prompt-login.html
code+id_token+token.config.dynamic.sign/OP-prompt-login.png
code+id_token+token.config.dynamic.sign/OP-prompt-none-LoggedIn.html
code+id_token+token.config.dynamic.sign/OP-prompt-none-NotLoggedIn.html
code+id_token+token.config.dynamic.sign/OP-redirect_uri-NotReg.html
code+id_token+token.config.dynamic.sign/OP-redirect_uri-NotReg.png
code+id_token+token.config.dynamic.sign/OP-Req-acr_values.html
code+id_token+token.config.dynamic.sign/OP-Req-claims_locales.html
code+id_token+token.config.dynamic.sign/OP-Req-id_token_hint.html
code+id_token+token.config.dynamic.sign/OP-Req-login_hint.html
code+id_token+token.config.dynamic.sign/OP-Req-max_age=1.html
code+id_token+token.config.dynamic.sign/OP-Req-max_age=1.png
code+id_token+token.config.dynamic.sign/OP-Req-max_age=10000.html
code+id_token+token.config.dynamic.sign/OP-Req-NotUnderstood.html
code+id_token+token.config.dynamic.sign/OP-Req-ui_locales.html
code+id_token+token.config.dynamic.sign/OP-request-Unsigned.html
code+id_token+token.config.dynamic.sign/OP-request_uri-Unsigned-Dynamic.html
code+id_token+token.config.dynamic.sign/OP-Response-code+id_token+token.html
code+id_token+token.config.dynamic.sign/OP-Response-Missing.html
code+id_token+token.config.dynamic.sign/OP-Response-Missing.png
code+id_token+token.config.dynamic.sign/OP-scope-address.html
code+id_token+token.config.dynamic.sign/OP-scope-All.html
code+id_token+token.config.dynamic.sign/OP-scope-email.html
code+id_token+token.config.dynamic.sign/OP-scope-phone.html
code+id_token+token.config.dynamic.sign/OP-scope-profile.html
code+id_token+token.config.dynamic.sign/OP-UserInfo-Body.html
```

code+id_token+token.config.dynamic.sign/OP-UserInfo-Endpoint.html
code+id_token+token.config.dynamic.sign/OP-UserInfo-Header.html
code+token.config.dynamic.sign/OP-claims-essential.html
code+token.config.dynamic.sign/OP-ClientAuth-Basic-Dynamic.html
code+token.config.dynamic.sign/OP-ClientAuth-SecretPost-Dynamic.html
code+token.config.dynamic.sign/OP-display-page.html
code+token.config.dynamic.sign/OP-display-popup.html
code+token.config.dynamic.sign/OP-IDToken-kid.html
code+token.config.dynamic.sign/OP-nonce-noncode.html
code+token.config.dynamic.sign/OP-nonce-NoReq-code.html
code+token.config.dynamic.sign/OP-OAuth-2nd-30s.html
code+token.config.dynamic.sign/OP-OAuth-2nd-Revokes.html
code+token.config.dynamic.sign/OP-OAuth-2nd.html
code+token.config.dynamic.sign/OP-prompt-login.html
code+token.config.dynamic.sign/OP-prompt-login.png
code+token.config.dynamic.sign/OP-prompt-none-LoggedIn.html
code+token.config.dynamic.sign/OP-prompt-none-NotLoggedIn.html
code+token.config.dynamic.sign/OP-redirect_uri-NotReg.html
code+token.config.dynamic.sign/OP-redirect_uri-NotReg.png
code+token.config.dynamic.sign/OP-Req-acr_values.html
code+token.config.dynamic.sign/OP-Req-claims_locales.html
code+token.config.dynamic.sign/OP-Req-id_token_hint.html
code+token.config.dynamic.sign/OP-Req-login_hint.html
code+token.config.dynamic.sign/OP-Req-max_age=1.html
code+token.config.dynamic.sign/OP-Req-max_age=1.png
code+token.config.dynamic.sign/OP-Req-max_age=10000.html
code+token.config.dynamic.sign/OP-Req-NotUnderstood.html
code+token.config.dynamic.sign/OP-Req-ui_locales.html
code+token.config.dynamic.sign/OP-request-Unsigned.html
code+token.config.dynamic.sign/OP-request_uri-Unsigned-Dynamic.html
code+token.config.dynamic.sign/OP-Response-code+token.html
code+token.config.dynamic.sign/OP-Response-Missing.html
code+token.config.dynamic.sign/OP-Response-Missing.png
code+token.config.dynamic.sign/OP-scope-address.html
code+token.config.dynamic.sign/OP-scope-All.html
code+token.config.dynamic.sign/OP-scope-email.html
code+token.config.dynamic.sign/OP-scope-phone.html
code+token.config.dynamic.sign/OP-scope-profile.html
code+token.config.dynamic.sign/OP-UserInfo-Body.html
code+token.config.dynamic.sign/OP-UserInfo-Endpoint.html
code+token.config.dynamic.sign/OP-UserInfo-Header.html

```
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf
```

2.1.4 OpenID Provider Publishing Configuration Information

In this example, the ProseWare organization is requesting certification of its "Humongous Identity" software to the 2.1.4 OpenID Provider Publishing Configuration Information profile on April 13, 2015. It submits this zip file as an attachment:

```
ProseWare-Humongous_Identity-OP-Config-13-Apr-2015.zip
```

with the following contents:

```
code.config.static.sign/OP-Discovery-claims_supported.html
code.config.static.sign/OP-Discovery-Config.html
code.config.static.sign/OP-Discovery-JWKs.html
code.config.static.sign/OP-Discovery-jwks_uri.html
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf
```

Note that if dynamic registration is supported, the ".static." in the log file paths above will instead be ".dynamic.".

2.1.5 Dynamic OpenID Provider

In this example, the ProseWare organization is requesting certification of its "Humongous Identity" software to the Dynamic OpenID Provider profile on April 13, 2015. It submits this zip file as an attachment:

```
ProseWare-Humongous_Identity-OP-Dynamic-13-Apr-2015.zip
```

with the following contents:

```
code.config.dynamic.sign/OP-ClientAuth-Basic-Dynamic.html
code.config.dynamic.sign/OP-ClientAuth-SecretPost-Dynamic.html
code.config.dynamic.sign/OP-Discovery-claims_supported.html
code.config.dynamic.sign/OP-Discovery-Config.html
code.config.dynamic.sign/OP-Discovery-JWKs.html
code.config.dynamic.sign/OP-Discovery-jwks_uri.html
code.config.dynamic.sign/OP-IDToken-RS256.html
code.config.dynamic.sign/OP-redirect_uri-Missing.html
code.config.dynamic.sign/OP-redirect_uri-Missing.png
code.config.dynamic.sign/OP-redirect_uri-Query-Added.html
code.config.dynamic.sign/OP-redirect_uri-Query-Added.png
```

```
code.config.dynamic.sign/OP-redirect_uri-Query-Mismatch.html
code.config.dynamic.sign/OP-redirect_uri-Query-Mismatch.png
code.config.dynamic.sign/OP-redirect_uri-Query-OK.html
code.config.dynamic.sign/OP-redirect_uri-RegFrag.html
code.config.dynamic.sign/OP-Registration-Dynamic.html
code.config.dynamic.sign/OP-Registration-Endpoint.html
code.config.dynamic.sign/OP-Registration-jwks.html
code.config.dynamic.sign/OP-Registration-jwks_uri.html
code.config.dynamic.sign/OP-Registration-logo_uri.html
code.config.dynamic.sign/OP-Registration-policy_uri.html
code.config.dynamic.sign/OP-Registration-Sector-Bad.html
code.config.dynamic.sign/OP-Registration-tos_uri.html
code.config.dynamic.sign/OP-request-Unsigned.html
code.config.dynamic.sign/OP-request_uri-Sig.html
code.config.dynamic.sign/OP-request_uri-Support.html
code.config.dynamic.sign/OP-request_uri-Unsigned-Dynamic.html
code.config.dynamic.sign/OP-Rotation-OP-Sig.html
code.config.dynamic.sign/OP-Rotation-RP-Sig.html
code.config.dynamic.sign/OP-UserInfo-RS256.html
OpenID-Certification-Attestation-Statement.pdf
OpenID-Certification-of-Conformance.pdf
OpenID-Certification-Terms-and-Conditions.pdf
```